



Acqua fredda
Cold water



Disinfestazione
Pest control



Sanificazione
Sanitizing



Gardening



Lancia getto rotante
Rotary lance

TSS®
Total Stop
SYSTEM

Caratteristiche Generali - General Features:

- Manico con avvolgitubo statico per tubo AP (6 m)
- Lancia Washing
- Lancia Spraying
- Pompa a 3 pistoni assiali comandati dal piattello oscillante, testa in alluminio
- Pistoni in acciaio inox temperato
- Valvola di sicurezza automatica con azzeramento della pressione nella testa pompa
- Motore universale elettrico con protezione termica e motore
- Lunghezza cavo elettrico 5 m
- Two-wheel trolley with handle and static hose reel (6 m HP hose)
- Washing lance
- Spraying lance
- 3 Axial stainless steel pistons wobble-plate pumps
- Tempered stainless steel pistons
- Automatic by-pass valve with pump head pressure discharge
- Single-phase universal motor with thermal protector
- Electric cable length 5 m

Fornito con - Equipped with:

WASHING MODE

Pistola
Trigger gun
46328



Testina getto regolabile
Adjustable jet nozzle
46540



Prolunga lancia
Lance extension
46332 (42 cm)



Testina getto rotante
Rotary jet nozzle
41565



Tubo AP 6 m
HP hose 6 m
46541 (6 m)



SPRAYING MODE

Tubo spiralato 6m
Spiral hose 6m
5340380



Testina porta ugello
head lead nozzle
5340360



Prolunga lancia
Lance extension
5340420



Ugello
nozzle
5340090



Pistola
Trigger gun
5340370



NEW

Dati Tecnici / Technical Data

MOD	COD		MAX							
			bar	psi				l/h	gph	kw
HU4600 DUAL SYSTEM	15221	SPRAYING MODE	4	58	0,3	0,08	0,035	50	220-240~	11,6
		WASHING MODE	160	2300	460	121	2,2	50	220-240~	

Temperatura massima acqua / Max inlet water temperature

50°C 122°F IPX5-S1